



SALES FACT SHEET

Equipped with the Award Winning **Comfort Control System™**



- Increased Reliability
- On-Board Diagnostics
- Fault Recall
- Active Protection™



R-410A

RAPM- JEZ

14.5 SEER Models
 Efficiencies up to 16.00 SEER
 Nominal Sizes 1 1/2 to 5 Tons
 [5.28 kW] to [17.6 kW]
Eight Models
 Cooling Capacities
 18,800 to 62,500 BTU/HR
 [5.50 kW] to [18.32 kW]

GENERAL TERMS OF LIMITED WARRANTY

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Compressor Ten (10) Years
 Any Other Part Ten (10) Years

RAPM- Series Conditional Replacement Warranty:

Rheem will provide a replacement model (if an exact replacement is not available, an equivalent product will be provided) to the original purchaser if the compressor fails within 5 years (providing the unit is installed with a new Rheem Air Handler OR Rheem Indoor Coil with a Rheem Gas Furnace, and is properly matched as specified by Rheem and/or listed in the Air Conditioning Institute (AHRI) published rating, and if additional conditions are satisfied. See product warranty card for additional information.



Features


The Rheem *Prestige® Series* RAPM- JEZ Condensing Units were designed with performance in mind. These units offer comfort, energy conservation and dependability for single, multi-family and light commercial applications.

- The *Comfort Control System™* provides on-board diagnostics and fault history for condensing units with single-phase compressors by detecting system and electrical problems without adding sensors. It can also communicate "fault codes" to enabled "L terminal" thermostats. The integrated diagnostics with *Active Protection* prevents compressor operation when potentially harmful conditions are detected.
- 7-Segment LED Display is exclusive only to Rheem products. The information-display quickly and accurately shows technicians the source of malfunctions.
- Five-year conditional unit replacement warranty.
- Compressor sound blanket is standard to provide quiet operation.
- Attractive, louvered wrap-around jacket protects the coil from yard hazards and weather extremes. Top grille is steel reinforced for extra strength. Cabinet is powder painted for all-weather protection.
- Air is discharged upward away from bushes and shrubs. The discharge pattern of the top grille provides minimum air restriction.
- Combination Grille/Motor Mount secures the motor to the underside of the discharge grille. The grille protects the motor windings and bearings from rain and snow.
- Removable top grille provides access to the condenser fan motor and condenser coil.
- Single speed 8-pole fan motor designed for low speed, quiet, energy-saving operation.
- All models meet or exceed a 1000-hour salt spray test per ASTM B117 Standard Practice for Operating Salt Spray Testing Apparatus.

<u>R</u>	<u>A</u>	<u>P</u>	<u>M</u>	<u>—</u>	<u>018</u>	<u>J</u>	<u>E</u>	<u>Z</u>
RHEEM	REMOTE CONDENSING UNIT	P = 14 SEER	DESIGN SERIES M = R-410A (2ND DESIGN SERIES)		COOLING CAPACITY 018= 18,000 BTU/HR [5.28 kW] 024= 24,000 BTU/HR [7.03 kW] 030= 30,000 BTU/HR [8.79 kW] 036= 36,000 BTU/HR [10.55 kW] 042= 42,000 BTU/HR [12.31 kW] 048= 48,000 BTU/HR [14.07 kW] 056= 56,000 BTU/HR [16.41 kW] 060= 60,000 BTU/HR [17.58 kW]	ELECTRICAL DESIGNATION J = 208/230V-1-60	VARIATIONS EQUIPPED WITH THE COMFORT CONTROL SYSTEM™	COOLING CONNECTION FITTING Z = SWEAT W/SCROLL

[] Designates Metric Conversions

Price	Starting at: \$
-------	--------------------



"Proper sizing and installation of equipment is critical to achieve optimal performance. Split system air conditioners and heat pumps must be matched with appropriate coil components to meet ENERGY STAR criteria. Ask your Contractor for details or visit www.energystar.gov."